

Tables

Specifications

Redisage PN		P01	P02
Ports	RS232	-	-
	RS485	-	-
	RS232/RS485	2x	2x
Microcontroller		ESP32	
WiFi		N/A	802.11 b/g/n 150 Mbps / 2.4 GHz
Bluetooth		N/A	v4.2 BR/EDR and BLE
SMA socket connector for WiFi/BT antenna		:x:	:white_check_mark:
Tactile switch		:white_check_mark:	:x:
Power	Voltage	12-30 VDC	
	Power	< 1 W	
Frame ground protection		yes	
Baud rate		up to 115200 bps	
LED indicators		power, link activity, programmable RGB	
RS485 termination		120 ohm manually enabled	

Redisage PN		P01	P02
Connector	RS232/RS485	8-pin terminal block max. 2.5 mm ² wire	
	Power	3-pin terminal block max. 2.5 mm ² wire	
	Ethernet	RJ45	
Transmission distance	RS485	max. 1,200 m at 9.6 kbps; max. 400 m at 115.2 kbps (Belden 9841 2P twisted-pair cable, if different cables are used, the transmission distance may change)	
	RS232	max. 15 m at 115.2 kbps	
Mounting and enclosure		DIN rail, plastic PA - UL 94 V0, black/green	
Temperatures		-40°C to +75°C operating and storage	
Humidity		10 - 90% RH, non-condensing	
ESD protection		±4 kV contact discharge / ±8 kV air discharge	
Certification		CE, RoHS	

Pin assignments

P01

P01

Open IoT Ethernet Gateway

012345678901234

Power: 12-30V/DC <1W

Temperature: -40°C +75°C

Port: 2xRS232/RS485 ETH

Ethernet: 10/100BaseT

MAC Add: #####MAC1#####

REV1 MADE IN EU

4	Vin	8	Tx2	12	A2	Ethernet RJ45
3	Gnd	7	Rx2	11	B2	
2	Din	6	Tx1	10	A1	
1	FG	5	Rx1	9	B1	

A1

B1

A2

B2

SC

220

SC

220

SC

Software Control

P02

P02

Open IoT Wi-Fi Ethernet Gateway

012345678901234

Power: 12-30V/DC <1W

Temperature: -40°C +75°C

Port: 2xRS232/RS485 ETH

Wi-Fi: 802.11b/g/n

Ethernet: 10/100BaseT

MAC Add: #####MAC1#####

REV1 MADE IN EU

4	Vin	8	Tx2	12	A2	Ethernet RJ45
3	Gnd	7	Rx2	11	B2	
2	Din	6	Tx1	10	A1	
1	FG	5	Rx1	9	B1	

A1

B1

A2

B2

SC

220

SC

220

SC

Software Control

Revision #9

Created 10 May 2024 10:37:55 by Jan Górski

Updated 26 July 2024 14:44:56 by Jan Górski